

Version number: 1

Replaces SDS: 2011-12-23

Issued: 2014-01-21

Not for sale in the USA

Section 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product identifier

Trade name

Matador

Article-no

Product/Article	Diameter(mm)	Packaging (kg)	Part Number
Matador 6011	3.2	20	30044
Matador 6011	4.0	20	30046
Matador 6011	5.0	20	35024
Matador 6013	3.2	20	30044
Matador 6013	4.0	20	30053
Matador 7018	3.2	20	30049
Matador 7018	4.0	20	30051
Matador 7018	5.0	20	35025
Matador 7018	2.5	20	35026

1.2 Relevant identified uses of the substance or mixture and uses advised against

Article type SMAW Un- and Low-alloyed electrodes Classification: AWS SFA 5.1/5.5 or other

Electric arc welding Use

1.3 Details of the supplier of the safety data sheet

Supplier Linde Philippines, Inc.

Street address 30F Wynsum Corporate Plaza # 22 F. Ortigas Jr. Avenue

Ortigas Center, Pasig City

Philippines

+63 (2) 883 9000 Telephone

> Fax +63 (2) 883 9000

Email customerservice.ph@linde.com

1.4 Emergency telephone number

Available outside office hours

Emergency phone number +63 (2) 702 7500

Other



Version number: 1

Replaces SDS: 2011-12-23

Issued: 2014-01-21

Additional product information

Web site: www.linde.com.ph (refer to website used in packaging)

Section 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1271/2008 [CLP] applicable

2.2 Label elements

Not applicable

2.3 Other hazards

When the product is used in the welding process the most important hazards are: Overexposure to fumes and gases from welding can be dangerous to health. Watch out for splatter, hot metal and slag. It may cause skin burn and cause fire.



Version number: 1

Replaces SDS: 2011-12-23

Issued: 2014-01-21

Section 3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances

This product is a mixture and please refer to Section 3.2

3.2 Mixtures

3.2 Mixtures						
Mild steel core	Fe	Mn	Cr	Ni	Cu	Si
Typical	8-99	<0.6	<0.1	<0.1	<0.1	<0.2
Flux coating	High Cellulose E6010, 6011	Rutile E6012, 6013	Basic Low Hydrogen E7016, 7018	Rutile Iron Powder E7024	Basic Iron Powder E7028	Cas No.
Limestone and/or Calcium Carbonate	-	<10	20-30	<10	10-20	1317-65-3
Magnesite (total inhalable dust) (respirable dust)	5-10	<5	-	-	-	546-93-0
Cellulose (total inhalable dust) (respirable dust)	25-60	<15	-	-	-	9004-34-6
Iron Oxides (as Fe)	<10	<10	<10	<10		1309-37-6
Inorganic Fluorides (as F	-	<10	10-30	<10	5-15	16984-48-8
Iron powder	-	<10	10-35	10-60	10-60	7439-89-6
Manganese and its Inorganic compounds (a Mn)	s 5-15	5-15	<15	<15	<10	7439-96-5 and others
Rutile/Titanium Dioxide (total inhalable dust) (respirable dust)	10-35	15-60	<10	10-30	<10	13463-67-7
Silicon and Silicon Alloys (as Si)	-	-	<5	<5	<5	7440-21-3
Silicate Binders	<5	<5	<5	<5	<5	1344-09-8
Mica (total inhalable dust) (respirable dust)	<5	<20	<5	<5	<5	12001-26-2
Quartz/Silica Respirable crystalline	<10	<15	5-60	<10	<5	14808-60-7
Kaolin (respirable dust)	-	<20	-	<5	<5	1332-58-7
Other Mineral Silicates	5-30	5-30	5-10	5-30	5-10	1332-58-7



Version number: 1

Replaces SDS: 2011-12-23

Issued: 2014-01-21

Section 4. FIRST AND MEASURES

4.1 Description of first aid measures

Inhalation IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for

breathing. Call a physician if symptoms occur.

Skin contact Burns should be treated by a doctor.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. Burns from radiation, see doctor.

Ingestion Contact a doctor if more than an insignificant amount has been swallowed.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons.

4.3 Indication of any immediate medical attention and special treatment needed

Not applicable

Section 5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2), powder or diffuse jet of water. In case of major fire: Extinguish fire with

diffuse jet of water or foam.

5.2 Special hazards arising from the substance or mixture

Not applicable

5.3 Advice for fire fighters

Special protective equipment for fire Wear self contained breathing apparatus

fighters

Section 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

General ventilation and local fume extraction must be adequate to keep fume concentrations within safe limits. Use respiratory equipment



Version number: 1

Replaces SDS: 2011-12-23

Issued: 2014-01-21

when welding in a confined space. Wear protective clothing and eye protection appropriate to arc welding. Skin contact should be avoided to prevent possible allergic reactions.

6.2 Environmental precautions

Try to prevent the material from entering drains or water courses.

6.3 Methods and material for containment and cleaning up

Not applicable

6.4 Reference to other sections

Personal protection see section 8 and for disposal see section 13. Environmental precautions, paragraph 12. See also section 7 Precautions for safe handling.

Section 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Preventive handling precautions	Ensure adequate ventilation for the welder and others. Use respiratory equipment when welding in
	a confined space. Wear protective clothing and eye protection appropriate to arc welding. Remove
	all flammable materials and liquids before welding.
General hygiene	Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Store welding consumables inside a room without humidity. Do not store welding consumables directly on the ground or beside walls. Store away from chemical substances like acids which could cause chemical reactions.

7.3 Specific end use(s)

Welding process.

Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Welding fume component	CAS No.	ES-TWA	ES-STEL
Total welding fume (particulate)	-	5	
Iron oxide fume (as Fe)	1309-37-1	5	10
Manganese and its inorganic compounds (as Mn)	7439-96-5	1	3
Silica, amorphous			
(total inhalable dust)	-	6	
(respirable dust)		2.4	



Version number: 1

Replaces SDS: 2011-12-23

Issued: 2014-01-21

Magnesium oxide (as Mg)
(total inhalable dust) 1309-48-4 10
(fume and respirable dust) 4 10
Titanium dioxide
(total inhalable dust) 13463-67-7 10
(respirable dust) 4
Calcium Oxide 1305-78-8 2
Calcium Silicate
(total inhalable dust) 1344-95-2 10
(respirable dust) 4
Fluoride, inorganic (as F) 16984-48-8 2.5
Nitrogen dioxide (NO ₂) 10102-44-0 3ppm 5ppm
Ozone (O ₃) 10028-15-6 0.2 ppm
Nitrogen monoxide (NO) 10102-43-9 25ppm 35ppm

8.2 Exposure controls

Environmental Exposure Control - Refer to Section 6 of this SDS

Technical precaution measures	General ventilation and local fume extraction must be adequate to keep fume concentration	
	within safe limits.	
Eye / face protection	Wear eye protection appropriate for welding.	
Safety gloves	Skin contact should be avoided to prevent possible allergic reactions.	
Other skin protection	$We ar body\ protection\ which\ helps\ to\ prevent\ injury\ from\ radiation,\ sparks\ and\ electric\ shock.$	
Respiratory protection	Use respiratory equipment when welding in a confined space. Wear protective clothing and eye	
	protection appropriate to arc welding.	

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance, colour	Grey
Appearance, physical state	Rod
Auto-ignition temperature	Not applicable
Auto-inflammability	Not auto-flammable
Decomposition temperature	Not applicable
Evaporation rate	Not applicable
Explosive properties	Not explosive
Flammability (solid gas)	Not applicable
Flash point	Not applicable



Version number: 1

Replaces SDS: 2011-12-23

Issued: 2014-01-21

Form Metal wire with flux coating

Initial boiling point and boiling range Not applicable

Melting point / Freezing point Not applicable

Odour Odourless

Odour threshold Not applicable

Oxidising properties Not applicable

Partition coefficient: n-octanol / water Not applicable

pH value Not applicable

Relative density Not applicable

Solubility Not applicable

Solubility in water Insoluble

Upper / lower flammability or Not applicable

explosive limits

Vapour density Not applicable
Vapour pressure Not applicable
Viscosity Not applicable

9.2 Other information

Not applicable

Other

Density 7.98g/cm³

Section 10. STABILITY AND REACTIVITY

10.1 Reactivity

Not applicable

10.2 Chemical stability

Stable at normal conditions.

10.3 Possibility of hazardous reactions

Not applicable

10.4 Conditions to avoid

None under normal conditions



Version number: 1

Replaces SDS: 2011-12-23

Issued: 2014-01-21

10.5 Incompatible materials

Not applicable

10.6 Hazardous decomposition products

Welding fumes and gases. Additional fume may arise from coatings and contaminants on the base material.

Welding fume component	CAS No.	Classification (67/548EEC)	CLP (1272/2008)		Concentration of classified fume components
Aluminium oxide (AI)	1344- 28-1	-	-	-	1.8 to 1.2
Barium (Ba)	7440- 39-3	-	-	-	≤0.1
Bismuth oxide (Bi)	12640- 40-3	-	-	-	≤0.1
Calcium (Ca)	1305- 78-8	-	-	-	0.1 to 11.6
Cobalt oxide	1307-	R22: Harmful if swallowed	Acute tox 4 (oral)	H302	≤0.1
(Co)	96-6	R43: May cause sensitisation by contact	Skin sens. 1	H317	
Chromium III compounds (as Cr)	24613- 89-6	R45: May cause cancer R35: Causes severe burns R43: May cause sensitisation by skin contact	Carc. 1B Skin Corr. 1A Skin Sens. 1	H350 H314 H317	≤0.1
Copper oxide (Cu)	1317- 38-0	-	-	-	≤0.1
Iron oxide (Fe)	1332- 37-2	-	-	-	11.9 to 54.9
Potassium (K)	7440- 09-7	R34: Causes burns	Skin Corr. 1B	H314	0.6 to 23.8
Lithium (Li)	7439- 93-2	R34: Causes burns	Skin Corr. 1B	H314	0.1 to 0.8
Magnesium oxide (Mg)	1309- 48-4	-	-	-	0.1 to 5.3



Version number: 1

Replaces SDS: 2011-12-23

Issued: 2014-01-21

Manganese (Mn)	7439- 96-5	-	-	-	0.7 to 8.2
Molybdenum (Mo)	7439- 98-7	Molybdenum trioxide R36/37: Irritating to eyes and respiratory system R40: Limited evidence of carcinogenic effect	Molybdenum trioxide Carc. 2 Eye Irrit. 2 STOT SE 3	H351 H319 H335	≤0.1
Sodium (Na)	7440- 23-5	R34: Causes burns	Skin Corr. 1B	H314	0.5 to 8.7
		R40: Limited evidence of carcinogenic effect R43: May cause sensitisation by	Carc. 2 Skin sens 1 STOT RE 1	H351 H317 H372	0.1 to 0.2
Nickel (Ni)	7440- 02-0	skin contact R48/23: Toxic danger of serious damage to health by prolonged exposure through inhalation R52/53: Harmful to aquatic organisms, may cause long-term			
		adverse effects in the aquatic environment			
Lead (Pb)	7439- 92-1	-	-	-	0.1 to 1.8
Silicon (Si)	7440- 21-3	-	-	-	2.1 to 16.3
Titanium dioxide (Ti)	13463- 67-7	-	-	-	0.1 to 3.2
Vanadium (V)	7440- 62-2	-	-	-	≤0.1



Version number: 1

Replaces SDS: 2011-12-23

Issued: 2014-01-21

Zinc (Zn)	7440- 66-6	-	-	-	0.1 to 3.5
Fluoride (F-)	16984- 48-8	-	-	-	0.1 to 21.4

Final fume classification					
Classification	H phrase	Text			
Skin corrosion/irritation: Category 1B	H314	Causes severe skin burns and eye damage			
Carcinogenicity: Category 1B	H350	May cause cancer			

The classification information above relates to the fume during use

Fume analysis: wt %	Fume analysis: wt %
AI 0.1 to 1.2	Ni 0.1 to 0.2
Ca 0.1 to 11.6	Pb 0.1 to 1.8
Fe 11.9 to 54.9	Si 2.1 to 16.3
K 0.6 to 23.8	Ti 0.1 to 3.2
Li 0.1 to 0.8	Zn 0.1 to 3.5
Mg 0.1 to 5.3	F- 0.1 to 21.4
Na 0.5 to 8.7	



Version number: 1

Replaces SDS: 2011-12-23

Issued: 2014-01-21

Section 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Conditions to avoid: none in the form supplied

When welding, fumes and gases generated can be dangerous to health.

Acute toxicology Excessive exposures may affect human health, as follows: Aspiration may cause pulmonary oedema

and pneumonitis Short-term overexposure can cause dizziness, nausea and irritation of the nose,

throat or eyes.

Irritation Not applicable

Corrosive effects Not applicable

Sensitisation May cause sensitisation by skin contact

Mutagenicity Not applicable

Carcinogenicity Welding fumes are possibly carcinogenic to humans

Repeated dose toxicity Not applicable
Reproductive toxicity Not applicable

Section 12. ECOLOGICAL INFORMATION

12.1 Toxicity

The welding process can effect the environment if fume is released directly into the atmosphere. Residues from welding consumables could degrade and accumulate into soils and ground water.

12.2 Persistence and degradability

Not applicable

12.3 Bio accumulative potential

Not available

12.4 Mobility in Soil

Not applicable

12.5 Results of PBT and vPvB assessment

Not applicable

12.6 Other adverse effects



Version number: 1

Replaces SDS: 2011-12-23

Issued: 2014-01-21

Not applicable

Section 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Disposal considerations Dispose of any product, residue or packing material according to national and local regulations. Spent

; fume extraction filters shall be disposed of as dangerous waste.

Other

Waste code 12 01 13 - welding waste

Section 14. TRANSPORT INFORMATION

14.1 UN number

Not applicable

14.2 UN proper shipping name

Not applicable

14.3 Transport hazard class(es)

Not applicable

14.4 Packing group

Not applicable

14.5 Environmental hazards

Not applicable

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Other

Dangerous goods No

Section 15. REGUATORY INFORMATION



Version number: 1

Replaces SDS: 2011-12-23

Issued: 2014-01-21

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture.

EU reguations

The product does not need to be labelled in accordance with EC directives or respective national laws.

National regulations

Refer to RULE 1100: GAS AND ELECTRIC WELDING AND CUTTING OPERATIONS, OCCUPATIONAL SAFETY

AND HEALTH STANDARDS (AS AMENDED, 1989)

15.2 Chemical safety assessment

Not applicable

Section 16. OTHER INFORMATION

References to key literature and Regulation (EC) No 1907/2006 of the European Parliament and of the Council, (REACH).

data sources Regulation (EC) No 1272/2008 of the European Parliament and of the Council.

EH40/2005 Workplace exposure limits.

The Waste regulations 2011 No.988

C&L Inventory database

Annex VI CLP Regulation (EC) 1272/2008

Phrase meaning H314 – Causes severe skin burns and eye damage

H350 - May cause cancer.

Other

Manufacturer's notes

Read this Safety Data Sheet carefully and become aware of hazards implied and the safety

information.

End of document